

LISTING OF CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in this application.

1. (previously presented) An implant for use in a patient's spinal column, said implant comprising:

a body portion having a length, a width, and a depth, and configured to be insertable between first and second bone segments, the body portion having an outer surface and an inner surface forming a hollow region, the hollow region comprising most of the volume of the body portion, the body portion further having first and second open ends;

wherein at least one of the first and second open ends comprises a single bone receiving channel extending there across that has a first depth measured from the trough of the channel to a first side of the outer surface at the at least one end, the first side extending along the length of the body portion, the channel also having a second depth measured from the trough of the channel to a second side of the outer surface at the at least one end, the second side extending along the length of the body portion, the second side opposite the first side, the first and second depths having different measurements, the channel configured to engage at least one of the first and second bone segments.

2. (previously presented) The implant of claim 1 wherein the perimeter of the outer surface of the implant is a substantially geometric shape.

3. (previously presented) The implant of claim 2 wherein the geometric shape is an ellipse.

4. (previously presented) The implant of claim 1 wherein the length ranges from about 11.5 to about 15.5 millimeters, the width ranges from about 8.0 to about 9.0 millimeters and the depth ranges from about 5.5 to about 6.5 millimeters.

5. (previously presented) The implant of claim 2 wherein the geometric shape is a circle.

6. (previously presented) The implant of claim 1 wherein the implant comprises a substantially tubular shape.

7. (previously presented) The implant of claim 1 wherein the implant is formed of bone allograft material.

8. (previously presented) The implant of claim 7 wherein at least a portion of one of the first and second ends comprises demineralized cortical bone.

9. (canceled)

10. (canceled)

11. (canceled)

12. (canceled)

13. (previously presented) The implant of claim 7 wherein the bone allograft material is obtained from a cross-section of a donor bone having an intermedullary canal, and wherein said inner surface of the implant is defined by the intermedullary canal of the donor bone.

14. (previously presented) The implant of claim 13 wherein the inner surface is configured such that the volume of the hollow region is greater than the intermedullary canal of the donor bone.

15. (previously presented) The implant of claim 1 further comprising:

a longitudinal axis, and

the bone receiving channel further comprises a centerline running parallel to the implant longitudinal axis dividing said ends, wherein the centerline of the bone receiving channel is offset from the longitudinal axis.

16. (previously presented) The implant of claim 1 wherein the bone receiving channel has a substantially concave arcuate shape.

17. (previously presented) The implant of claim 1 wherein both first and second ends comprise a bone receiving channel and both bone receiving channels have a substantially concave arcuate shape.

18. (previously presented) The implant of claim 1 wherein the bone receiving channel comprises at least two angled faces.

19. (previously presented) The implant of claim 1 further comprising at least one surface defining a hole in communication with said outer surface and said inner surface, suitable for attaching a suture to secure said implant to at least one of said first and second bone segments.

20. (previously presented) The implant of claim 1 wherein the implant is fabricated of biocompatible metal.

21. (previously presented) The implant of claim 1 wherein the implant is fabricated of biocompatible polymer.

22. (canceled)

23. (currently amended) An implant for use in a patient's spinal column, said implant comprising:

a body portion having a longitudinal axis and configured to be insertable between first and second bone segments, the body portion having an outer surface and an inner surface defining a substantially hollow portion, said body portion further having first and second ends open to said hollow portion and orthogonal to said longitudinal axis, said first and second ends comprising concave cutouts configured to engage and retain said first and second bone segments, the cutouts each comprising a centerline running parallel to the implant longitudinal axis and dividing each of the cutouts,

wherein the centerline of the cutout of the first end is offset from the implant longitudinal axis in one direction, and the centerline of the cutout of the second end is offset from the implant longitudinal axis in the opposite direction; and

wherein the implant is formed of bone allograft material obtained from a cross-section of a donor bone having an intermedullary canal, and said inner surface is configured such that the volume of said substantially hollow portion is greater than the intermedullary canal of the donor bone.

24. (previously presented) The implant of claim 23, wherein at least one cutout further comprises at least two angled faces.

25. (previously presented) The implant of claim 23 wherein the at least one cutout has a substantially concave arcuate shape.

26. (canceled)

27. (canceled)

28. - 52. (canceled)

53. (currently amended) An implant for use in a patient's spinal column, said implant comprising:

a body portion having a length, a width, a depth and a longitudinal axis, and configured to be insertable between first and second cut bone segments, the body portion having an outer surface and an inner surface defining a substantially hollow portion, the body portion further having first and second ends open to said hollow portion and orthogonal to said longitudinal axis, at least one of the first and second ends comprising a cutout configured to engage and retain at least one of the first and second cut

bone segments, the cutout comprising a centerline running parallel to the implant longitudinal axis
dividing said ends, wherein the centerline of the at least one cutout is offset from the longitudinal axis;

wherein the implant is formed of bone allograft material obtained from a cross-section of a donor bone having an intermedullary canal, and said inner surface is defined by the intermedullary canal of the donor bone.

54. (previously presented) The implant of claim 53 wherein the perimeter of the outer surface of the implant is a substantially geometric shape.

55. (previously presented) The implant of claim 54 wherein the geometric shape is an ellipse.

56. (previously presented) The implant of claim 54 wherein the geometric shape is a circle.

57. (previously presented) The implant of claim 53 wherein the length ranges from about 11.5 to about 15.5 millimeters, the width ranges from about 8.0 to about 9.0 millimeters and the depth ranges from about 5.5 to about 6.5 millimeters.

58. (previously presented) The implant of claim 53 wherein the implant comprises a substantially tubular shape.

59. (canceled)

60. (currently amended) The implant of claim ~~53-59~~ wherein at least a portion of at least one of said first and second ends is comprised of demineralized cortical bone.

61. (canceled)

62. (currently amended) The implant of claim 53-59 wherein ~~the bone allograft material is obtained from a cross section of a donor bone having an intermedullary canal, and~~ said inner surface is configured such that the volume of said substantially hollow portion is greater than the intermedullary canal of the donor bone.

63. (previously presented) The implant of claim 53 wherein the at least one cutout has a substantially concave arcuate shape.

64. (previously presented) The implant of claim 53 wherein both the first and second ends comprise cutouts and both cutouts have a substantially concave arcuate shape.

65. (previously presented) The implant of claim 53 wherein the at least one cutout comprises at least two angled faces.

66. (previously presented) The implant of claim 53 further comprising at least one surface defining a hole in communication with said outer surface and said inner surface, suitable for attaching a suture to secure said implant to at least one of said first and second bone segments.

67. (canceled)

68. (canceled)

69. (previously presented) An implant for use in a patient's spinal column, the implant comprising:

a tubular body having a length, a width, and a depth, and an outer surface and an inner surface forming a thin tubular wall, the perimeter of the outer surface having a substantially oval, circular, or elliptical shape, the body further having first and second open ends; wherein:

at least one of the first and second ends comprises a single channel extending there across that has a first depth measured from the trough of the channel to a first side of the outer surface at the at least one end, the first side extending along the length of the tubular body, the channel also having a second depth measured from the trough of the channel to a second side of the outer surface at the at least one end, the second side extending along the length of the tubular body, the second side opposite the first side, the first and second depths having different measurements, the channel configured to engage a bone segment.

70. (previously presented) The implant of claim 69 wherein the length ranges from about 11.5 to about 15.5 millimeters, the width ranges from about 8.0 to about 9.0 millimeters, and the depth ranges from about 5.5 to about 6.5 millimeters.

71. (previously presented) The implant of claim 69 wherein the tubular wall has a thickness of about 1.0 millimeters.

72. (canceled)

73. (canceled)

74. (canceled)